

BASEFIX

WATER-BASED ACRYLIC PIGMENTABLE TRANSPIRING
COVERING FIXING PRIMER
FOR PLASTER, PREMIXES, CONCRETE
AND PLASTERBOARD FOR INTERIOR AND EXTERIOR USE



GRANTS *LEED* CREDITS

CHARACTERISTICS		ENVIRONMENTAL	METHOD OF USE			PRECAUTIONS
ALLOWS TO BREATHE	WATER BASED	ECO GREEN	SPRAY APPLICATION	APPLY BY BRUSH	APPLY BY ROLLER	STORAGE: KEEP AWAY FROM FROST

PROBLEM

FOR REINFORCING AND UNIFORMING SURFACE ABSORPTION. FOR IMPROVING THE COVERAGE OF THE NEXT COAT



Concrete, masonry and plasterboard surfaces often need a primer before being painted, which:

- fixes the surface, to prevent outcrops and eliminates dust;
- is coloured, to increase the coverage of the next coat of paint or coating without altering the surface's transpirability.

SOLUTION

BASEFIX is a water-based acrylic pigmented primer.

Its formulation guarantees excellent penetration and grip to the surface while maintaining excellent transpirability and the product can be coloured in a mixing (tinting) system.

APPLICATION FIELDS

BASEFIX is suitable for plaster, premixes, concrete and plasterboard, for interior and exterior use.

ADVANTAGES

- Water-based.
- Single product with 3 functions: reinforcing, uniforming and improving coverage.
- Can be coloured in a mixing (tinting) system.

METHOD OF USE

• SURFACE PREPARATION

The surface must be clean and dry and free from crumbling or brittle and loose parts.

In case of mould or algae infestation, pre-treat with SANICLEAN and then SANIPROTECT. For surfaces with old paint always check the adhesion.

• APPLICATION

BASEFIX is ready to use, therefore only needs remixing into a uniform consistency.

Any leftover product can be kept for many months according to climate conditions, in properly closed packaging. It can be diluted with maximum 20% water.

BASEFIX can be applied with a brush, roller or spray gun in a single coat.

• CONSUMPTION

For very absorbent surfaces: 150 g/m².

For low absorption surfaces: 100 g/m².

• PRECAUTIONS

- Application temperature from +5°C to +35°C.
- Do not add any other materials such as cement, aggregates or additives.
- In hot periods, avoid fast drying of the product for at least 24 hours.
- Do not apply on dirty or dusty surfaces.
- Straight after application clean the tools with water and the coated surfaces with a damp cloth.
- Store in original closed packaging in a dry place.

TECHNICAL CHARACTERISTICS

	Standard	BASEFIX
Appearance		Liquid
Colour		White vedi mazzetta colori "LONG LIFE COLOURS" - INDEX
Density	EN 2811-1	1.20 ± 0.10 kg/L
pH		7-8
Storage in original packaging in a dry place (keep away from frost)		12 months
Workability characteristics		
Dilution		use as such, up to a dilution with water max 20%
Waiting time - till tack-free drying (*)		approx 6 ÷ 8 hours
Waiting time - for deep draying (*)		approx 24 hours
Application temperature		+3°C ÷ +35°C
Application		manual or mechanical
Performance characteristics		
	Standard	Product performance
Permeability to water vapour	EN 7783-2	Sd <0.14 m

(*) The stated times may be longer or shorter as the temperature decreases or increases.

see **LONG LIFE COLOURS** colour swatch



the numerous possible uses and the possible interference of conditions or elements beyond our control, we assume no responsibility regarding the results which are obtained. The purchasers, of their own accord and under their own responsibility, must establish the suitability of the product for the envisaged use.

The figures shown are average indicative figures relevant to current production and may be changed or updated by INDEX at any time without previous warning. The advice and technical information provided, is what results from our best knowledge regarding the properties and the use of the product. Considering

PACKAGING

5-litre Pail.

• FOR ANY FURTHER INFORMATION OR ADVICE ON PARTICULAR APPLICATIONS, CONTACT OUR TECHNICAL OFFICE • IN ORDER TO CORRECTLY USE OUR PRODUCTS, REFER TO INDEX TECHNICAL SPECIFICATIONS •

<p>Construction Systems and Products</p> <p>Via G. Rossini, 22 - 37060 Castel D'Azzano (VR) - Italy - C.P.67 T. +39 045 8546201 - F. +39 045 518390</p>	<p>Internet: www.index-spa.com Informazioni Tecniche Commerciali tecom@indexspa.it Amministrazione e Segreteria index@indexspa.it Index Export Dept. index.export@indexspa.it</p>		<p>TOTAL QUALITY index</p>	<p>Environmental Management Systems index</p>		
--	--	--	---------------------------------------	--	--	--